


# RCB SERIES

BIG BORE ROTARY TABLES

**TSUDAKOMA**

# RCB SERIES







\*Other motors & rpm available

• Dimensions = mm

\*\*Booster optional

Specifications subject to change without notice

Table Model		RCB-350	RCB-450	RCB- 550
Versions available		R,L	R,L	R,L
Table diameter		350	450	550
Center height		255	310	350
Center bore	Nose Diameter	245H7	295H7	345H7
	Thru Diameter	215	265	315
Table T-slot width		14H7	14H7	18H7
Guide block width		18h7	18h7	18h7
Servo motor*		Alpha 12i	Alpha 22i	Alpha 22i
Maximum motor speed rpm		3,000	3,000	3,000
Speed reduction ratio		1/90	1/90	1/120
Maximum table speed rpm		33.3	33.3	33.3
Inertia converted into motor shaft x 10 <sup>-3</sup> kg.m <sup>2</sup>		3.48	6.14	6.01
Clamp system**		Hydraulic		
Clamp torque @500psi Nm (ft. lbs.)		3,300 (2,432)	4,700 (3,464)	6,500 (4,790)
Indexing accuracy arc sec.		±7.5		
Repeatability arc sec.		±2		
Net Weight kg (lbs.)		400 (880)	520 (1,144)	720 (1,584)
Allowable wheel torque Nm (ft. lbs.)		1,942 (1,431)	3,276 (2,414)	4,716 (3,475)
Allowable work inertia kg.m <sup>2</sup>		6.1	17.7	37.8
Allowable work weight [with tailstock]	 kg (lbs)	400 (880)	700 (1,540)	1,000 (2200)
	 N (lbf)	29,400 (6,586)	45,000 (10,080)	54,000 (12,096)
	 Nm (ft. lbs.)	3,300 (2,432)	4,700 (3,464)	6,500 (4,790)
	 Nm (ft. lbs.)	3,626 (2,672)	8,000 (5,896)	15,132 (11,152)

## Dimensions

